

Lifting stati. Aqualift F XL 300l Duo, SPF 4500-S1

Article information

Item no.: 11123
GTIN: 4026092057902
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: duo pump
Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage
Installation situation: free-standing installation
System type: Duo

Dimensions

Net weight: 200 kg
Gross weight: 220 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Tank volume: 300 l

Pumping device

Pump: SPF 4500
Number of pumps: 2

Length of mains cable for pump:	5 m
Operating mode:	S1
Type of fuse required (electrical protection):	3 x C 25 A
Impeller type:	Multi-vane impeller
Free passage:	40 mm
Control	
Control unit:	Comfort
Level measurement instrument:	Immersion pipe
Type of level measurement:	pneumatic
Mains frequency:	50 Hz
Operating voltage:	400 V