

## Comfort control unit 400V, Aqualift Mono, 4.0-6.3 A

### Article information

Item no.: 28756  
GTIN: 4026092055014  
Price group: 20

### Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

### Description

Komfort control unit for lifting stations or pumping stations. Suitable for 400 V single stations. Optional connection option for float switches, conductivity probes and level probe on the terminal strip. User-friendly menu navigation in multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of the current measured values. Simple adjustment of the function-related parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signals via optional potential-free contact or integrated serial interface for GSM modem.

#### Variant

Series: ab 03/2010  
Type of system: Single unit

#### General characteristics

Colour: grey  
System type: Mono  
ATEX: no

#### Dimensions

Net weight: 2,47 kg  
Gross weight: 3,19 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Rated current: 4 - 6,3 A

Control	Comfort
Control unit:	yes
Motor protection switch:	yes
Protection class control unit:	IP 54
Potential-free contact:	yes
GSM interface:	yes
USB interface:	no
Log book function:	yes
Multi-line display:	yes
Battery buffering:	yes
Self-diagnosis system (SDS):	yes