

Replacement pump KTP 300 for Minilift

Article information

Item no.: 28836
GTIN: 4026092000922
Price group: 90

Description

Replacement pump for sewage-free wastewater

Variant

Pump control: Float switch

General characteristics

Standard: EN 12050-2
Type of wastewater: without sewage
Cable length: 5 m

Dimensions

Net weight: 4,21 kg
Gross weight: 4,49 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: KTP 300
Connection type: Schuko (earthed contact) 2-pin
Operating voltage: 230 V
Mains frequency: 50 Hz
Rated current: 1,9 A
Protection class: I
Insulation class: F
Protection class (pump): IP 68 (3m)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 35 °C
Max. pumping height: 6 m
Speed: 2800 U/min
Power P1: 0,34 kW
Power P2: 0,21 kW
Operating mode: S1
Type of fuse required (electrical protection): C 16 A
Type of pump connection cable: H07RN-F 3G 1.5 mm²
Length of mains cable for pump: 5 m

Control

Connection type:

Type of fuse required (electrical protection):

Schuko (earthed contact) 2-pin

C 16 A