

Basement drain DN 100, Black grating, Class K 3

Article information

Item no.: 29111
GTIN: 4026092007846
Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:	yes
Position of lateral connection:	Type II
Sealing water height:	60 mm
Discharge rate (l/s) with 20 mm threshold:	1,8

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Odour trap:	included

Dimensions

Vertical adjustment:	30 - 90 mm
Net weight:	2,55 kg
Gross weight:	2,88 kg
Cutout dimension, width:	320 mm
Cutout dimension, length:	400 mm
Installation depth:	216 - 276 mm
Type of height adjustability:	vertically adjustable upper section
Length:	380 mm
Width:	290 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Inlet nominal size (DN):	70 mm
--------------------------	-------

Number of inlets:	2
Material of drain body:	PP
Socket version:	lateral
Coverage features	
Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	188 mm
Length of cover:	188 mm
Frame material:	Polymer
Locking:	placed
Load class:	K 3 (EN 1253-1)
Rim width:	200 mm
Rim length:	200 mm
Upper section material:	Polymer
Contents of sludge trap:	yes