

The Superflat bathroom drain Variofix, DN50, slotted cover

Article information

Item no.: 42701.50
GTIN: 4026092028605
Price group: 10

Advantages

- Movable outlet socket
- Lip seal fixed on the drain body
- Side inlet via odour trap

Description

The Superflat bathroom drain is suitable for indoor floor drainage. The drain made of PP is equipped with a secure, reliably installed seal as well as a removable odour trap.

Variant

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to DIN 18534
Sealing water height: 30 mm
Discharge rate (l/s) with 20 mm threshold: 0,8

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
Odour trap: included

Dimensions

Vertical adjustment: 10 - 23 mm
Net weight: 1,35 kg
Gross weight: 1,59 kg
Cutout dimension, width: 180 mm
Cutout dimension, length: 260 mm
Type of height adjustability: vertically adjustable upper section
Length: 312 mm
Width: 312 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1
Inlet nominal size (DN): 40 mm

Number of inlets:	1
Material of drain body:	PP
Coverage features	
Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	95 mm
Length of cover:	95 mm
Surface:	Polished SST
Frame material:	Stainless steel 14301
Locking:	placed
Load class:	K 3 (EN 1253-1)
Rim width:	132 mm
Rim length:	132 mm
Shape of upper section:	square
Upper section material:	PP