

Scada wall drain w/cov, Wave, 304 SST, fixed w/prf membrn

Article information

Item no.: 48000.03M
GTIN: 4026092079133
Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory
- Alternative odour trap Multistop

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant

Lighting:

Waterproofing layer on the drain body:

Water exposure class in accordance to DIN 18534-1 (up to and including):

Sealing water height:

Discharge rate (l/s) with 20 mm threshold:

without

Factory-fitted sealing collar (WaD) according to DIN 18534

W3-I

22 mm

0,5

General characteristics

Nominal size (DN):

50

Outer diameter (OD):

58 mm

Odour trap:

included

Dimensions

Net weight:

1,86 kg

Gross weight:

2,35 kg

Length:

362 mm

Width:

195 mm

Height:

353 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Tank/drain body

Number of outlets:

1

Material of drain body:

ABS

Coverage features

Type of cover:

Cover material:

Colour of cover:

Height of cover:

Length of cover:

Min. flooring height:

Surface:

Frame material:

Locking:

Grating design:

Max. flooring height:

Shape of upper section:

Upper section material:

Scada drain cover

Stainless steel 14301

silver

74 mm

312 mm

15 mm

Brushed SST

ABS

inserted

Wave

19 mm

square

ABS