

## Yard drain System 100, vert., slot grat., B 125

### Article information

Item no.: 67110B  
GTIN: 4026092039373  
Price group: 10

### Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

### Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

#### Variant

System: 100  
Contents of sludge trap: yes

#### General characteristics

Nominal size (DN): 100  
Odour trap: no

#### Dimensions

Net weight: 2,9 kg  
Gross weight: 2,9 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Tank/drain body

Number of outlets: 1  
Material of drain body: Polymer  
Socket version: vertical

#### Coverage features

Type of cover: Round slotted cover  
Cover material: Ecoguss  
Colour of cover: black

|                          |                |
|--------------------------|----------------|
| Width of cover:          | 247 mm         |
| Length of cover:         | 247 mm         |
| Surface:                 | EDM            |
| Locking:                 | Lock & Lift    |
| Load class:              | B 125 (EN 124) |
| Shape of upper section:  | square         |
| Upper section material:  | Ecoguss        |
| Contents of sludge trap: | yes            |