

## Grease separator EasyClean free Basic, NS 4, Direct, left

### Article information

Item no.: 94004.10DL  
GTIN: 4026092084076  
Price group: 60

### Advantages

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work. There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|   |        |
|---|--------|
| Direction of flow:                        | left   |
| Disposal variant:                         | Direct |
| Sludge bucket:                            | no     |
| Nominal size (NS):                        | 4      |
| Refill inlet in accordance with DIN 1988: | no     |
| Type of disposal:                         | manual |
| Load-bearing capacity (DIN 19901):        | F3     |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Standard:               | EN 1825   |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:      | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

#### Dimensions

|                      |         |
|----------------------|---------|
| Net weight:          | 103 kg  |
| Gross weight:        | 133 kg  |
| Set-up area, length: | 1960 mm |
| Set-up area, width:  | 800 mm  |
| Set-up area, height: | 1420 mm |

|   |   |
|---|---|
| Required access area, length:               | 1960 mm   |
| Required access area, width:                | 700 mm  |
| Required access area, height:               | 1420 mm   |
| Packaging dimension:                        | length  |
| Packaging dimension:                        | width   |
| Packaging dimension:                        | height  |
| <br>  |   |
| Tank/drain body                             |   |
| Nominal pressure (PN):                      | 10  |
| Pressure pipe connection (DN):              | 65  |
| Pressure pipe connection (OD):              | 75 mm   |
| Distance pipe bottom outlet to tank bottom: | 985 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1055 mm   |
| Outlet nominal size (OD):                   | 110 mm  |
| Outlet nominal size (DN):                   | 100 mm  |
| Inlet nominal size (OD):                    | 110 mm  |
| Inlet nominal size (DN):                    | 100 mm  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| <br>  |   |
| Coverage features                           |   |
| Type of cover:                              | Cover   |
| Cover material:                             | Polymer   |
| Colour of cover:                            | violet  |
| Locking:                                    | Quick-release closure   |
| Tightness:                                  | odour-tight   |
| <br>  |   |
| Wastewater contents                         |   |
| Max. grease layer thickness:                | 180 mm  |
| Total volume:                               | 820 l   |
| Contents of sludge trap:                    | 400 l   |
| Storage quantity of grease:                 | 160 l   |