

## Shell Kit for Pumpfix F, without nozzles, tileable

### Article information

Item no.: 24000X-RBK  
GTIN: 4026092097052  
Price group: 30

### Description

KESSEL shell kit for Pumpfix F, without sockets, tileable

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating a Pumpfix F backwater pumping station.

#### General characteristics

|                            |  |
|----------------------------|--|
| Colour:                    | black  |
| Type of wastewater:        | with sewage  |
| Installation situation:    | floor slab installation  |
| Delivery state:            | Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected) |
| Approval:                  | Z-53.2-388   |
| Motor type:                | KSM 140  |
| Type de protection moteur: | IP 68 (3m/48h)   |
| ATEX:                      | no   |
| Odour trap:                | Multistop  |

#### Dimensions

|  |                                     |
|--|-------------------------------------|
| Net weight:  | 13,74 kg                            |
| Gross weight:  | 16,55 kg                            |
| Groundwater resistant from lower edge of base section: | 3000 mm                             |
| Cutout dimension, width:                               | 750 mm                              |
| Cutout dimension, length:                              | 750 mm                              |
| Vertical drop between inlet and outlet:                | 9 mm                                |
| Installation depth:                                    | 516 - 669 mm                        |
| Type of height adjustability:                          | vertically adjustable upper section |
| Packaging dimension:                                   | length                              |
| Packaging dimension:                                   | width                               |
| Packaging dimension:                                   | height                              |

Tank/drain body

Socket version: optional

## Coverage features

|                       |                      |
|-----------------------|----------------------|
| Type of cover:        | tileable cover plate |
| Cover material:       | Polymer              |
| Width of cover:       | 366 mm               |
| Length of cover:      | 366 mm               |
| Drainage function:    | yes                  |
| Locking:              | Lock & Lift          |
| Load class:           | K 3 (EN 1253-1)      |
| Max. flooring height: | 16 mm                |