

## Technology kit Aqualift S Comp GTF1200Res Duo Tronic

### Article information

Item no.: 281230C-TK  
GTIN: 4026092108055  
Price group: 20

### Description

For combination with a KESSEL shell kit for creating a Duo lifting station for wastewater without sewage with a GTF1200 wastewater pump.

The ready to plug in lifting station for wastewater without sewage is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an open pump tank. One-handed closures enable easy removal of the integrated components. The system for installation in the floor slab is pre-assembled for final installation on site. The station is controlled by a user-friendly control unit, which is optionally integrated in the building management system using a potential-free contact or alarm and collective fault messages that can be output through a GSM interface.

### KESSEL technology kit consisting of:

- Pumps with multi-vane vortex impeller for maximum operating safety
- Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems
- Comfort control unit 230 V
- Optical alarm probe
- Pneumatic level measurement

#### Variant

Type of system:	duo pump
Resistant:	Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems
Pump control:	Control unit

#### General characteristics

ATEX:	no
-------	----

#### Dimensions

Net weight:	25 kg
Gross weight:	25 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device	
Pump:	GTF 1200 resistant
Number of pumps:	2
Connection type:	coded plug
Rated current:	6,2 A
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping capacity:	15,5 m <sup>3</sup> /h
Max. pumping height:	9 m
Speed:	2650 U/min
Power P1:	1,4 kW
Power P2:	0,84 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	30 mm
Length of mains cable for pump:	5 m
Control	
Control unit:	Comfort
Alarm sensor:	optical probe
Level measurement instrument:	Immersion pipe
Type of level measurement:	pneumatic
Protection class control unit:	IP 54
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug
Length of mains cable for control unit:	1,4 m
Potential-free contact:	optional
GSM interface:	yes
USB interface:	yes
Log book function:	yes
Multi-line display:	yes
Battery buffering:	yes
Self-diagnosis system (SDS):	yes
Rated current:	6,2 A
Type of fuse required (electrical protection):	C 16 A