

Comfort control unit 400V, Aqualift Mono, 4.0-6.3 A

Article information

Item no.: 28756
GTIN: 4026092055014
Price group: 20

Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

Description

Komfort control unit for lifting stations or pumping stations. Suitable for 400 V single stations. Optional connection option for float switches, conductivity probes and level probe on the terminal strip. User-friendly menu navigation in multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of the current measured values. Simple adjustment of the function-related parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signals via optional potential-free contact or integrated serial interface for GSM modem.

Variant	
Series:	ab 03/2010
Type of system:	Single unit

General characteristics	
Colour:	grey
System type:	Mono
ATEX:	no

Dimensions	
Net weight:	2,47 kg
Gross weight:	3,19 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device	
Rated current:	4 - 6,3 A

Control

Control unit:
Motor protection switch:
Protection class control unit:
Potential-free contact:
GSM interface:
USB interface:
Log book function:
Multi-line display:
Battery buffering:
Self-diagnosis system (SDS):

Comfort

yes
IP 54
yes
yes
no
yes
yes
yes
yes