

Practicus basement drain DN 100, Black grating, Vertical outlet

Article information

Item no.: 34102

GTIN: 4026092047705

Price group: 10

Advantages

• Vertically adjustable upper section

Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap: yes
Discharge rate (l/s) with 10 mm threshold: 1,1
Discharge rate (l/s) with 20 mm threshold: 1,8

General characteristics

Standard: EN 1253-2
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: no

Dimensions

Net weight: 1,33 kg
Gross weight: 1,55 kg
Cutout dimension, width: 180 mm
Cutout dimension, length: 180 mm
Installation depth: 221 - 277 mm

Type of height adjustability: vertically adjustable upper section

Length:150 mmWidth:150 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1

Material of drain body: Polymer Socket version: vertical



Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Dolymer

138 mm

Frame material:

Polymer

Polymer

Locking:

Polymer

Load class: K 3 (EN 1253-1)

Shape of upper section: square
Upper section material: Polymer
Contents of sludge trap: yes