

Scada wall drain w/cov, conc, fixed w/prf membrn

Article information

Item no.: 48000.01M
GTIN: 4026092079119
Price group: 10

Advantages

- Flexible & convenient installation options
- Membrane flange attached in the factory
- Alternative odour trap Multistop

Description

The Scada wall drain is suitable for indoor floor drainage and provides connection options at the front, left and right-hand side.

Variant

Lighting:

without

Waterproofing layer on the drain body:

Factory-fitted sealing collar (WaD) according to DIN 18534

Water exposure class in accordance to DIN 18534-1 (up to and including):

W3-I

Sealing water height:

22 mm

Discharge rate (l/s) with 20 mm threshold:

0,5

General characteristics

Nominal size (DN):

50

Outer diameter (OD):

58 mm

Odour trap:

included

Dimensions

Net weight:

1,8 kg

Gross weight:

2,31 kg

Length:

362 mm

Width:

195 mm

Height:

353 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Tank/drain body

Number of outlets:

1

Material of drain body:

ABS

Coverage features

Type of cover:	Scada drain cover
Colour of cover:	selectable
Height of cover:	61 mm
Length of cover:	296 mm
Min. flooring height:	15 mm
Frame material:	Stainless steel 14301
Locking:	inserted
Grating design:	Invisible
Max. flooring height:	15 mm
Shape of upper section:	square
Upper section material:	ABS