

## Yard drain System 200, horiz., slot grat., B 125

### Article information

Item no.: 67923B  
GTIN: 4026092038819  
Price group: 10

### Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

### Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

#### Variant

|                                            |     |
|--------------------------------------------|-----|
| System:                                    | 200 |
| Contents of sludge trap:                   | yes |
| Discharge rate (l/s) with 20 mm threshold: | 4,5 |

#### General characteristics

|                    |     |
|--------------------|-----|
| Nominal size (DN): | 100 |
| Odour trap:        | no  |

#### Dimensions

|                      |             |
|----------------------|-------------|
| Vertical adjustment: | 40 - 150 mm |
| Net weight:          | 3,96 kg     |
| Gross weight:        | 4,36 kg     |
| Packaging dimension: | length      |
| Packaging dimension: | width       |
| Packaging dimension: | height      |

#### Tank/drain body

|                         |         |
|-------------------------|---------|
| Number of outlets:      | 1       |
| Material of drain body: | Polymer |
| Socket version:         | lateral |

#### Coverage features

|                |                     |
|----------------|---------------------|
| Type of cover: | Round slotted cover |
|----------------|---------------------|

|                          |                |
|--------------------------|----------------|
| Cover material:          | Ecoguss        |
| Colour of cover:         | black          |
| Width of cover:          | 258 mm         |
| Length of cover:         | 258 mm         |
| Surface:                 | EDM            |
| Frame material:          | Ecoguss        |
| Locking:                 | Lock & Lift    |
| Load class:              | B 125 (EN 124) |
| Rim width:               | 258 mm         |
| Rim length:              | 258 mm         |
| Shape of upper section:  | square         |
| Upper section material:  | Ecoguss        |
| Contents of sludge trap: | yes            |