

Replacement pump pumping station dry installation SPF 4500-S3

Article information

Item no.: 680533
GTIN: 4026092074947
Price group: 90

Description

Replacement pump type SPF 4500-S3 for Aqualift F XL pumping station, dry installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight: 26,5 kg
Gross weight: 29,3 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: SPF 4500
Connection type: Direct connection
Operating voltage: 400 V
Mains frequency: 50 Hz
Rated current: 7,5 A
Protection class: I
Insulation class: F
Cos phi - power factor: 0,85
Protection class (pump): IP 68
Temperature monitoring: controlled via control unit
Max. temperature (permanent) of conveyed material: 40 °C
Max. pumping height: 20 m
Speed: 2850 U/min
Power P1: 4,2 kW
Power P2: 3,5 kW
Operating mode: S3 - 50 %
Type of fuse required (electrical protection): Fuse protection through control unit 400 V
Type of pump connection cable: H07RN-F 7G 1.5 mm²
Length of mains cable for pump: 10 m

Control

Connection type:

Type of fuse required (electrical protection):

Direct connection

Fuse protection through control unit 400 V