

## Replacement pump Aquadive GTF1200 with float switch, 10 m

### Article information

Item no.: 680594  
GTIN: 4026092078808  
Price group: 90

### Description

Replacement pump, Aquadive GTF 1200 with floater for pumping station

#### Variant

Pump control: Float switch

#### General characteristics

Cable length: 10 m

#### Dimensions

Net weight: 11,44 kg

Gross weight: 11,44 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

#### Pumping device

Pump: GTF 1200

Connection type: Schuko (earthed contact) 2-pin

Operating voltage: 230 V

Mains frequency: 50 Hz

Rated current: 6,2 A

Protection class: I

Insulation class: F

Cos phi - power factor: 0,98

Protection class (pump): IP 68

Max. temperature (permanent) of conveyed material: 35 °C

Max. pumping height: 9 m

Speed: 2650 U/min

Power P1: 1,4 kW

Power P2: 0,84 kW

Operating mode: S3 - 50 %

Type of fuse required (electrical protection): C 16 A

Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>

Length of mains cable for pump: 10 m

#### Control

Connection type: Schuko (earthed contact) 2-pin

Type of fuse required (electrical protection): C 16 A