

## Replacement pump GTF 600 with float switch, 10 m

### Article information

Item no.: 680963  
GTIN: 4026092095386  
Price group: 90

### Description

Replacement pump with float switch for wastewater containing faecal matter.

#### Variant

Pump control: Float switch

#### General characteristics

Type of wastewater: without sewage

#### Dimensions

Net weight: 6,85 kg

Gross weight: 6,85 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

#### Pumping device

Pump: GTF 600

Connection type: Schuko (earthed contact) 2-pin

Operating voltage: 230 V

Mains frequency: 50 Hz

Rated current: 2,9 A

Protection class (pump): IP 68 (3m)

Max. temperature (permanent) of conveyed material: 40 °C

Max. pumping height: 8 m

Speed: 2750 U/min

Power P1: 0,65 kW

Power P2: 0,4 kW

Operating mode: S1

Type of fuse required (electrical protection): C 16 A

Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>

Impeller type: Multi-vane impeller

Length of mains cable for pump: 10 m

#### Control

Connection type: Schuko (earthed contact) 2-pin

Type of fuse required (electrical protection): C 16 A