

Replacement pump GTF 1250 w. float switch, Aqualift S 100/200, 5m

Article information

Item no.: 680978
GTIN: 4026092095911
Price group: 90

Description

Replacement pump with float switch for faecal-free wastewater.

Variant

Pump control: **Float switch**

General characteristics

Type of wastewater: **without sewage**

Dimensions

Net weight: **10,5 kg**
Gross weight: **10,5 kg**
Packaging dimension: **length**
Packaging dimension: **width**
Packaging dimension: **height**

Pumping device

Pump: **GTF 1250**
Connection type: **Schuko (earthed contact) 2-pin**
Operating voltage: **230 V**
Mains frequency: **50 Hz**
Rated current: **5,4 A**
Protection class (pump): **IP 68 (3m)**
Max. temperature (permanent) of conveyed material: **40 °C**
Max. pumping height: **11 m**
Speed: **2700 U/min**
Power P1: **1,3 kW**
Power P2: **0,8 kW**
Operating mode: **S3 - 50 %**
Type of fuse required (electrical protection): **C 16 A**
Type of pump connection cable: **H07RN-F 3G 1.5 mm²**
Impeller type: **Multi-vane impeller**
Length of mains cable for pump: **5 m**

Control

Connection type: **Schuko (earthed contact) 2-pin**

Type of fuse required (electrical protection): C 16 A