

## Yard drain System 400, DN 150, A, 380 - 510 mm

### Article information

Item no.: 851150A  
GTIN: 4026092004340  
Price group: 10

### Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

### Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

#### Variant

System: 400  
Heating: without  
Contents of sludge trap: yes  
Discharge rate (l/s) with 20 mm threshold: 4,5

#### General characteristics

Colour: black  
Standard: EN 752  
Nominal size (DN): 150  
Outer diameter (OD): 160 mm  
Odour trap: no

#### Dimensions

Net weight: 10 kg  
Gross weight: 10 kg  
Groundwater resistant from lower edge of base section: 500 mm  
Cutout dimension, width: 535 mm  
Cutout dimension, length: 585 mm  
Min. insertion depth: 55 mm  
Installation depth: 380 - 510 mm  
Type of height adjustability: vertically adjustable upper section  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

Tank/drain body  
Number of outlets: 1  
Material of drain body: Polymer  
Socket version: lateral

Coverage features

Type of cover: Round slotted cover  
Cover material: Polymer  
Colour of cover: black  
Width of cover: 400 mm  
Length of cover: 400 mm  
Surface: EDM  
Load class: A 15 (EN 124)  
Rim width: 400 mm  
Rim length: 400 mm  
Shape of upper section: square  
Contents of sludge trap: yes