

## Yard drain System 400, DN 150, D, 730 - 1080 mm

### Article information

Item no.: 851152D  
GTIN: 4026092004425  
Price group: 10

### Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

### Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

|                                            |         |
|--------------------------------------------|---------|
| Variant                                    |         |
| System:                                    | 400     |
| Heating:                                   | without |
| Contents of sludge trap:                   | yes     |
| Sealing water height:                      | 100 mm  |
| Discharge rate (l/s) with 20 mm threshold: | 4,5     |

|                         |          |
|-------------------------|----------|
| General characteristics |          |
| Colour:                 | black    |
| Standard:               | EN 752   |
| Nominal size (DN):      | 150      |
| Outer diameter (OD):    | 160 mm   |
| Odour trap:             | included |

|                                                        |                                     |
|--------------------------------------------------------|-------------------------------------|
| Dimensions                                             |                                     |
| Net weight:                                            | 50 kg                               |
| Gross weight:                                          | 50 kg                               |
| Groundwater resistant from lower edge of base section: | 500 mm                              |
| Cutout dimension, width:                               | 535 mm                              |
| Cutout dimension, length:                              | 585 mm                              |
| Min. insertion depth:                                  | 55 mm                               |
| Installation depth:                                    | 730 - 1080 mm                       |
| Type of height adjustability:                          | vertically adjustable upper section |
| Packaging dimension:                                   | length                              |
| Packaging dimension:                                   | width                               |
| Packaging dimension:                                   | height                              |

|                          |                     |
|--------------------------|---------------------|
| Tank/drain body          |                     |
| Number of outlets:       | 1                   |
| Material of drain body:  | Polymer             |
| Socket version:          | lateral             |
| Coverage features        |                     |
| Type of cover:           | Round slotted cover |
| Cover material:          | Grey iron           |
| Colour of cover:         | black               |
| Width of cover:          | 450 mm              |
| Length of cover:         | 450 mm              |
| Surface:                 | EDM                 |
| Load class:              | D 400 (EN 124)      |
| Rim width:               | 450 mm              |
| Rim length:              | 450 mm              |
| Shape of upper section:  | square              |
| Contents of sludge trap: | yes                 |