

## Chamber module LW 1000 floor slab Access LW 600, 880-1129 mm, Class D

### Article information

Item no.: 8740013  
GTIN: 4026092065280  
Price group: 60

### Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

### Description

The chamber module for wet installation is equipped with all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section.

The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, a taper, upper section and cover.

#### Variant

Note on installation depth: A load distribution slab must be installed on site for load class D

#### General characteristics

Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	underground installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Approval:	Z-42.1-527
ATEX:	no

#### Dimensions

Net weight:	108,5 kg
Gross weight:	125 kg
Groundwater resistant from lower edge of base section:	3000 mm
Installation depth:	880 - 1129 mm
Type of height adjustability:	vertically adjustable upper section

Length: 1200 mm  
Width: 1200 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

Tank/drain body  
Inlet max. scoring (DN): 150 mm  
Clear width of tank (LW): 1000 mm  
Clear width of entry (LW): 600 mm

#### Coverage features

Type of cover: Round cover plate  
Cover material: Grey iron  
Colour of cover: black  
Width of cover: 659 mm  
Height of cover: 122 mm  
Length of cover: 659 mm  
Surface: Grey iron  
Locking: locked  
Load class: D 400 (EN 124)  
Tightness: surface water resistant