

## Grease separat. EasyClean Modular free, NS 2, Direct, 3-part, TS

## **Article information**

Item no.: 93002-D1-R2-TS GTIN: 4026092104033

Price group: 60

## **Advantages**

- Ideal where access is tight
- can be divided into 3 parts for insertion, for an insertion opening of max. 66 cm
- Direct disposal with the tank closed

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

Variant

Chamber system: three-piece chamber

Disposal variant:

Shredder-Mix-System:

Sludge bucket:

Nominal size (NS):

SonicControl:

Direct

no

no

Disposal system: Disposal connection

Refill inlet in accordance with DIN 1988: no Type of disposal: manual

General characteristics

Material: PE Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 95 kg Gross weight: 113 kg



Height tank bottom up to centre section:

Required access area, length:

Required access area, width:

Required access area, height:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

S50 mm

1240 mm

580 mm

length

width

Packaging dimension:

height

Tank/drain body

Distance pipe bottom outlet to tank bottom: 715 mm
Distance pipe bottom inlet to tank bottom: 785 mm
Outlet nominal size (OD): 110 mm
Outlet nominal size (DN): 100 mm
Inlet nominal size (OD): 110 mm
Inlet nominal size (DN): 100 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 380 l Contents of sludge trap: 200 l

Control

Control unit: no