

Grease separator EasyClean ground NS 7, Auto Mix, 1475-1665 mm, D

Article information

Item no.: 93007/170D-DSP-TS

GTIN: 4026092103272

Price group: 60

Advantages

- Program-controlled rinsing device
- Customisation possible through control unit
- Low-maintenance operation

Description

The separator for greasy wastewater for underground installation consists of a grease separator and an engineering chamber. The two-piece system made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and an integrated sampling device. Access for cleaning and maintenance work is provided by inspection openings, with polymer upper sections for continuously adjustable height and level compensation. The innovative Shredder-Mix-System with integrated macerating system is responsible for homogenising and circulating the tank contents. Cleaning takes place via an exterior submersible pump which is installed in a separate engineering chamber and can be disconnected from the tank by a shut-off valve. A direct disposal pipe socket is available for odour-neutral manual disposal. The fully automatic program run is controlled by a user-friendly control unit with multi-line display that can be integrated into the building management system through a potential-free contact. The control unit with 10 m long cable is installed in the engineering chamber in the factory. Cleaning and disposal can be started remotely using the remote control. Thanks to the customisable cleaning program with fast-selection function, cleaning can be adapted to the local circumstances as required. Observance of the Drinking Water Hygiene Directive can be guaranteed through the fully automatic rinsing of the drinking water pipes. The refill inlet and solenoid valves must be installed in a dry room on site. The connections between the grease separator and the engineering chamber as well as the reserve conduits and the connections must be made on site. (see connection set 917421). A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL. 20 year polyethylene warranty.

Variant

Note on installation depth:

Ground installation frost-free depth 1700 mm

Shut-off valve:

yes

Disposal variant:

Auto Mix

Shredder-Mix-System:

yes

Sludge bucket:	no
Nominal size (NS):	7
SonicControl:	no
Disposal system:	Disposal connection
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	automatic cleaning system
Water supply:	2 solenoid valves 1"
Sampling device:	Type NBG
Load-bearing capacity (DIN 19901):	E4
General characteristics	
Material:	PE
Standard:	EN 1825
Installation situation:	underground installation
Delivery state:	Installation-ready (electrical components, connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection
Dimensions	
Net weight:	870 kg
Gross weight:	890 kg
Diameter:	659 mm
Max. length:	3965 mm
Installation depth:	1475 - 1665 mm
Type of height adjustability:	vertically adjustable upper section, can be tilted by 5 degrees
Required access area, length:	2540 mm
Required access area, width:	1235 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	995 mm
Distance pipe bottom inlet to tank bottom:	1100 mm
Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150 mm
Inlet nominal size (OD):	160 mm
Inlet nominal size (DN):	150 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	600 mm
Coverage features	
Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Locking:	locked

Load class: D 400 (EN 124)
 Tightness: odour-tight and surface water resistant

Wastewater contents 1100 l
 Separator contents: 1800 l
 Total volume: 700 l
 Contents of sludge trap: 280 l
 Storage quantity of grease:

Pumping device
 Pump: SPF 300 IP68
 Number of pumps: 1
 Weight, pump: 44 kg
 Connection type: Direct connection
 Rated current: 6,2 A
 Length of mains cable for pump: 5 m
 Protection class: I
 Insulation class: F
 Protection class (pump): IP 68
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 40 °C
 Max. pumping capacity: 60 m³/h
 Max. pumping height: 17 m
 Speed: 2850 U/min
 Power P1: 3,6 kW
 Power P2: 3 kW
 Operating mode: S2 - 30 min.
 Type of fuse required (electrical protection): Fuse protection through control unit 400 V
 Type of pump connection cable: H07RN-F 7G 1.5 mm²
 Impeller type: Radial impeller with macerating system

Control
 Control unit: yes
 Motor protection switch: yes
 Type of fuse required (RCD): 30 mA
 Protection class control unit: IP 54
 Mains frequency: 50 Hz
 Operating voltage: 400 V
 Connection type: Direct connection
 Potential-free contact: yes
 GSM interface: no
 USB interface: no
 Log book function: yes
 Multi-line display: yes
 Battery buffering: no
 Self-diagnosis system (SDS): yes
 Rated current: 6,2 A