

## EasyClean round grease separator free, NS 15, Standard

## **Article information**

## **Advantages**

Item no.: 93015.05

GTIN:

Price group: 60

• Low-maintenance operation

## Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal takes place with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:

Shredder-Mix-System:

no
Sludge bucket:

Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

Standard

no

no

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Set-up area, length:

Set-up area, width:

Set-up area, width:

Set-up area, height:

Set-up area, height:

Set-up area, height:

2020 mm

Required access area, length:

Required access area, width:

Required access area, height:

2020 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom: 1550 mm
Distance pipe bottom inlet to tank bottom: 1620 mm
Outlet nominal size (OD): 200 mm
Outlet nominal size (DN): 200 mm



Inlet nominal size (OD): 200 mm Inlet nominal size (DN): 200 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 2300 l
Total volume: 3800 l
Contents of sludge trap: 1500 l
Storage quantity of grease: 600 l

Control

Control unit: no