

## Grease separator EasyClean free NS 35, Direct

### Article information

Item no.: 93035.01/D  
GTIN: 4026092103685  
Price group: 60

### Advantages

- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. 20 year polyethylene warranty.

#### Variant

|   |        |
|---|--------|
| Disposal variant:                         | Direct |
| Shredder-Mix-System:                      | no     |
| Sludge bucket:                            | no     |
| Nominal size (NS):                        | 35     |
| SonicControl:                             | no     |
| Refill inlet in accordance with DIN 1988: | no     |
| Type of disposal:                         | manual |
| Load-bearing capacity (DIN 19901):        | F3     |

#### General characteristics

|                    |   |
|--------------------|---|
| Material:          | PE  |
| Standard:          | EN 1825   |
| Delivery state:    | Installation-ready (connection parts must be connected on site) |
| Scope of delivery: | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

#### Dimensions

|                               |         |
|-------------------------------|---------|
| Set-up area, length:          | 6480 mm |
| Set-up area, width:           | 1500 mm |
| Set-up area, height:          | 1662 mm |
| Required access area, length: | 6000 mm |
| Required access area, width:  | 1500 mm |
| Required access area, height: | 1662 mm |

#### Tank/drain body

|                                |       |
|--------------------------------|-------|
| Nominal pressure (PN):         | 10    |
| Pressure pipe connection (DN): | 65    |
| Pressure pipe connection (OD): | 75 mm |

|   |  |
|---|--|
| Distance pipe bottom outlet to tank bottom: | 1130 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1200 mm  |
| Outlet nominal size (OD):                   | 250 mm   |
| Outlet nominal size (DN):                   | 250 mm   |
| Inlet nominal size (OD):                    | 250 mm   |
| Inlet nominal size (DN):                    | 250 mm   |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes<br>in accordance with DIN 19560, PP or AS |

#### Coverage features

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | black                 |
| Locking:         | Quick-release closure |
| Tightness:       | odour-tight           |

#### Wastewater contents

|                             |        |
|-----------------------------|--------|
| Separator contents:         | 4500 l |
| Total volume:               | 8000 l |
| Contents of sludge trap:    | 3500 l |
| Storage quantity of grease: | 1400 l |

#### Control

|               |    |
|---------------|----|
| Control unit: | no |
|---------------|----|