

## Grease separator EasyClean free Basic, NS 10, Std, rt, Insp wind

### Article information

Item no.: 94010.21R  
GTIN: 4026092084274  
Price group: 60

### Advantages

- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

|                                           |                          |
|-------------------------------------------|--------------------------|
| Direction of flow:                        | right                    |
| Disposal variant:                         | Standard                 |
| Sludge bucket:                            | yes                      |
| Nominal size (NS):                        | 10                       |
| Refill inlet in accordance with DIN 1988: | no                       |
| Type of disposal:                         | manual with suction hose |
| Sampling device:                          | no                       |
| Load-bearing capacity (DIN 19901):        | F3                       |

#### General characteristics

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Material:               | PE                                                              |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |

#### Dimensions

|                               |          |
|-------------------------------|----------|
| Net weight:                   | 168,5 kg |
| Gross weight:                 | 203,5 kg |
| Set-up area, length:          | 2610 mm  |
| Set-up area, width:           | 965 mm   |
| Set-up area, height:          | 1670 mm  |
| Required access area, length: | 2610 mm  |
| Required access area, width:  | 965 mm   |
| Required access area, height: | 1670 mm  |
| Packaging dimension:          | length   |

|                                             |                                                                                              |
|---------------------------------------------|----------------------------------------------------------------------------------------------|
| Packaging dimension:                        | width                                                                                        |
| Packaging dimension:                        | height                                                                                       |
| Tank/drain body                             |                                                                                              |
| Nominal pressure (PN):                      | 10                                                                                           |
| Pressure pipe connection (DN):              | 65                                                                                           |
| Pressure pipe connection (OD):              | 75 mm                                                                                        |
| Distance pipe bottom outlet to tank bottom: | 1185 mm                                                                                      |
| Distance pipe bottom inlet to tank bottom:  | 1255 mm                                                                                      |
| Outlet nominal size (OD):                   | 160 mm                                                                                       |
| Outlet nominal size (DN):                   | 150 mm                                                                                       |
| Inlet nominal size (OD):                    | 160 mm                                                                                       |
| Inlet nominal size (DN):                    | 150 mm                                                                                       |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes<br>in accordance with DIN 19560, PP or AS |
| Coverage features                           |                                                                                              |
| Type of cover:                              | Cover                                                                                        |
| Cover material:                             | Polymer                                                                                      |
| Colour of cover:                            | violet                                                                                       |
| Locking:                                    | Quick-release closure                                                                        |
| Tightness:                                  | odour-tight                                                                                  |
| Wastewater contents                         |                                                                                              |
| Max. grease layer thickness:                | 230 mm                                                                                       |
| Total volume:                               | 1880 l                                                                                       |
| Contents of sludge trap:                    | 1000 l                                                                                       |
| Storage quantity of grease:                 | 400 l                                                                                        |