

EasySink sediment separator free, NS 1

Article information

Item no.: 97201/000
GTIN: 4026092026830
Price group: 60

Advantages

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

Description

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work. 20 year polyethylene warranty.

Variant

Nominal size (NS): 1
Type of disposal: manual with suction hose

General characteristics

Material: PE
Installation situation: free-standing installation
Delivery state: Installation-ready (connection parts must be connected on site)
Wastewater-resistant: resistant to aggressive wastewater

Dimensions

Net weight:	19 kg
Gross weight:	23 kg
Set-up area, length:	660 mm
Set-up area, width:	400 mm
Set-up area, height:	470 mm
Required access area, length:	570 mm
Required access area, width:	400 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body	
Distance pipe bottom outlet to tank bottom:	195 mm
Distance pipe bottom inlet to tank bottom:	305 mm
Outlet nominal size (OD):	50 mm
Outlet nominal size (DN):	50 mm
Inlet nominal size (OD):	50 mm
Inlet nominal size (DN):	50 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	305 mm
Volume of collecting tank:	13 l
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	370 mm
Length of cover:	370 mm
Locking:	Quick-release closure
Tightness:	odour-tight
Odour trap:	included
Control	
Control unit:	no