

## EasySink sediment separator free, NS 1

### Article information

Item no.: 97201/000  
GTIN: 4026092026830  
Price group: 60

### Advantages

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

### Description

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work. 20 year polyethylene warranty.

#### Variant

Nominal size (NS): 1  
Type of disposal: manual with suction hose

#### General characteristics

Material: PE  
Installation situation: free-standing installation  
Delivery state: Installation-ready (connection parts must be connected on site)  
Wastewater-resistant: resistant to aggressive wastewater

#### Dimensions

Net weight: 19 kg  
Gross weight: 23 kg  
Set-up area, length: 660 mm  
Set-up area, width: 400 mm  
Set-up area, height: 470 mm  
Required access area, length: 570 mm  
Required access area, width: 400 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

Tank/drain body	
Distance pipe bottom outlet to tank bottom:	195 mm
Distance pipe bottom inlet to tank bottom:	305 mm
Outlet nominal size (OD):	50 mm
Outlet nominal size (DN):	50 mm
Inlet nominal size (OD):	50 mm
Inlet nominal size (DN):	50 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	305 mm
Volume of collecting tank:	13 l
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	370 mm
Length of cover:	370 mm
Locking:	Quick-release closure
Tightness:	odour-tight
Odour trap:	included
Control	
Control unit:	no