

EasySink sediment separator ground, NS 1, Load class A

Article information

Item no.: 97201/00A
GTIN: 4026092026847
Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers. 20 year polyethylene warranty. Options:

Hole diameter of sediment tank

Variant

Nominal size (NS):

1

Type of disposal:

manual with suction hose

General characteristics

Material:

PE

Installation situation:

underground installation

Delivery state:

Installation-ready (connection parts must be connected on site)

Dimensions

Net weight:

25 kg

Gross weight:

31,67 kg

Groundwater resistant from lower edge of base section:

500 mm

Installation depth:

55 - 405 mm

Type of height adjustability:

vertically adjustable upper section, can be tilted by 5 degrees

Required access area, length:

1100 mm

Required access area, width:

532 mm

| | |
|---|---|
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| | |
| Tank/drain body | |
| Distance pipe bottom outlet to tank bottom: | 380 mm |
| Distance pipe bottom inlet to tank bottom: | 528 mm |
| Outlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 mm |
| Inlet nominal size (OD): | 110 mm |
| Inlet nominal size (DN): | 100 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |
| Clear width of entry (LW): | 400 mm |
| Volume of collecting tank: | 12 l |
| | |
| Coverage features | |
| Type of cover: | Cover plate |
| Cover material: | Polymer |
| Colour of cover: | black |
| Width of cover: | 364 mm |
| Height of cover: | 46 mm |
| Length of cover: | 364 mm |
| Locking: | locked |
| Load class: | A 15 (EN 124) |
| Tightness: | odour-tight and surface water resistant |
| Odour trap: | included |
| Control | |
| Control unit: | no |