

## EasySink sediment separator ground, NS 1, Class D

### Article information

Item no.: 97201/00D  
GTIN: 4026092026861  
Price group: 60

### Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank

### Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers. 20 year polyethylene warranty. Options:

Hole diameter of sediment tank

#### Variant

Nominal size (NS):

1

Type of disposal:

manual with suction hose

Load-bearing capacity (DIN 19901):

E4

#### General characteristics

Material:

PE

Installation situation:

underground installation

Delivery state:

Installation-ready (connection parts must be connected on site)

#### Dimensions

Net weight:

25 kg

Gross weight:

31,67 kg

Groundwater resistant from lower edge of base section:

500 mm

Installation depth:

55 - 405 mm

Type of height adjustability:

vertically adjustable upper section, can be tilted by 5 degrees

Required access area, length:

1100 mm

Required access area, width:	532 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	380 mm
Distance pipe bottom inlet to tank bottom:	528 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	400 mm
Volume of collecting tank:	12 l
Coverage features	
Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Width of cover:	395 mm
Height of cover:	52 mm
Length of cover:	395 mm
Locking:	locked
Load class:	D 400 (EN 124)
Tightness:	odour-tight and surface water resistant
Odour trap:	included
Control	
Control unit:	no