

## EasySink sediment separator free, NS 2

### Article information

Item no.: 97202/000  
GTIN: 4026092026885  
Price group: 60

### Advantages

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

### Description

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work. 20 year polyethylene warranty.

#### Variant

Nominal size (NS): 2  
Type of disposal: manual with suction hose

#### General characteristics

Material: PE  
Installation situation: free-standing installation  
Delivery state: Installation-ready (connection parts must be connected on site)  
Wastewater-resistant: resistant to aggressive wastewater

#### Dimensions

Net weight: 50,65 kg  
Gross weight: 59,45 kg  
Set-up area, length: 985 mm  
Set-up area, width: 650 mm  
Set-up area, height: 598 mm  
Required access area, length: 800 mm  
Required access area, width: 650 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

Tank/drain body	
Distance pipe bottom outlet to tank bottom:	255 mm
Distance pipe bottom inlet to tank bottom:	373 mm
Outlet nominal size (OD):	75 mm
Outlet nominal size (DN):	70 mm
Inlet nominal size (OD):	75 mm
Inlet nominal size (DN):	70 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Volume of collecting tank:	51 l
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	630 mm
Length of cover:	630 mm
Locking:	Quick-release closure
Tightness:	odour-tight
Odour trap:	included
Control	
Control unit:	no