

Grease separat. EasyClean Modular ground, NS 2, Standard, D

Article information

Item no.: 98202/00D
GTIN: 4026092027097
Price group: 60

Advantages

- Vertically adjustable upper section with odour-tight cover plates in various load classes
- Waterproof, resistant to aggressive wastewater
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (NS 4 with separate sludge trap tank) and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|--------------------------|
| Chamber system: | modular chamber |
| Disposal variant: | Standard |
| Shredder-Mix-System: | no |
| Sludge bucket: | no |
| Nominal size (NS): | 2 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual with suction hose |
| Load-bearing capacity (DIN 19901): | E4 |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Standard: | DIN 4040-100 |
| Installation situation: | underground installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|---------------|--------|
| Net weight: | 190 kg |
| Gross weight: | 190 kg |

| | |
|--|---|
| Groundwater resistant from lower edge of base section: | 500 mm |
| Max. length: | 1355 mm |
| Height tank bottom up to centre section: | 750 mm |
| Height centre section to top edge of tank: | 750 mm |
| Installation depth: | 330 - 480 mm |
| Type of height adjustability: | vertically adjustable upper section, can be tilted by 5 degrees |
| Required access area, length: | 1300 mm |
| Required access area, width: | 1300 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| | |
| Tank/drain body | |
| Distance pipe bottom outlet to tank bottom: | 1136 mm |
| Distance pipe bottom inlet to tank bottom: | 1236 mm |
| Outlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 mm |
| Inlet nominal size (OD): | 110 mm |
| Inlet nominal size (DN): | 100 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |
| Clear width of entry (LW): | 600 mm |
| | |
| Coverage features | |
| Type of cover: | Cover plate |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Width of cover: | 659 mm |
| Height of cover: | 121 mm |
| Length of cover: | 659 mm |
| Locking: | locked |
| Load class: | D 400 (EN 124) |
| Tightness: | odour-tight and surface water resistant |
| | |
| Wastewater contents | |
| Separator contents: | 945 l |
| Total volume: | 1145 l |
| Contents of sludge trap: | 200 l |
| Storage quantity of grease: | 80 l |
| | |
| Control | |
| Control unit: | no |