

## Replacement pump KTP/SPZ 1000 230 V, cable length 5 m

### Article information

Item no.: 28351  
GTIN: 4026092038420  
Price group: 90

### Description

Replacement pump with macerator for wastewater with sewage

#### Variant

Pump control: Control unit

#### General characteristics

Standard: EN 12050-1  
Type of wastewater: with sewage

#### Dimensions

Net weight: 10,29 kg  
Gross weight: 10,62 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: SPZ 1000  
Connection type: coded plug  
Operating voltage: 230 V  
Mains frequency: 50 Hz  
Rated current: 5,2 A  
Protection class: I  
Insulation class: F  
Cos phi - power factor: 0,97  
Protection class (pump): IP 68 (3m/48h)  
Temperature monitoring: integrated  
Max. temperature (permanent) of conveyed material: 35 °C  
Max. pumping height: 10 m  
Speed: 2800 U/min  
Power P1: 1,2 kW  
Power P2: 0,7 kW  
Operating mode: S3 - 50 %  
Type of fuse required (electrical protection): Fuse protection through control unit 230 V  
Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>  
Impeller type: Macerator  
Length of mains cable for pump: 5 m

Control

Connection type:

coded plug

Type of fuse required (electrical protection):

Fuse protection through control unit 230 V