

## Submersible pump Aquadive KTP 300 with float switch, 10m

### Article information

Item no.: 28840  
GTIN: 4026092000939  
Price group: 20

### Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

### Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

#### Variant

Pump control: **Float switch**

#### General characteristics

Material: **Polymer**  
Standard: **EN 12050-2**  
Type of wastewater: **without sewage**  
Cable length: **10 m**  
ATEX: **no**

#### Dimensions

Net weight: **4,61 kg**  
Gross weight: **4,89 kg**  
Length: **275 mm**  
Width: **390 mm**  
Height: **216 mm**  
Packaging dimension: **length**  
Packaging dimension: **width**  
Packaging dimension: **height**

#### Wastewater contents

Pressure pipe connection: **R 1 "**

#### Pumping device

Pump:	KTP 300
Number of pumps:	1
Weight, pump:	4 kg
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	1,6 A
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Length of mains cable for pump:	10 m

**Control**

Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A