

Basement drain DN 100, Black grating, Class K 3

Article information

Item no.: 29111
GTIN: 4026092007846
Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap: yes
Position of lateral connection: Type II
Sealing water height: 60 mm
Discharge rate (l/s) with 20 mm threshold: 1,8

General characteristics

Standard: EN 1253-1
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: included

Dimensions

Vertical adjustment: 30 - 90 mm
Net weight: 2,55 kg
Gross weight: 2,88 kg
Cutout dimension, width: 320 mm
Cutout dimension, length: 400 mm
Installation depth: 216 - 276 mm
Type of height adjustability: vertically adjustable upper section
Length: 380 mm
Width: 290 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Inlet nominal size (DN): 70 mm

Number of inlets: 2
Material of drain body: PP
Socket version: lateral

Coverage features

Type of cover: Slotted cover
Cover material: Polymer
Colour of cover: black
Width of cover: 188 mm
Length of cover: 188 mm
Frame material: Polymer
Locking: placed
Load class: K 3 (EN 1253-1)
Rim width: 200 mm
Rim length: 200 mm
Upper section material: Polymer
Contents of sludge trap: yes