

Upper section, Linearis Compact L: 550 mm, Sys 100, 304 SST cover, K 3

Article information

Item no.: 47806S
GTIN: 4026092079928
Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Variant

System:

100

Seepage opening:

yes

Waterproofing layer on the upper section:

Enclosed sealing collar to be glued (bd) according to DIN 18534

Water exposure class in accordance to DIN 18534-1 (up to and including):

W3-I

Sealing water height:

50 mm

Discharge rate (l/s) with 10 mm threshold:

0,6

Discharge rate (l/s) without threshold:

0,5 mm

General characteristics

Nominal size (DN):

100

Outer diameter (OD):

100 mm

ATEX:

no

Odour trap:

included

Dimensions

Net weight:

1,56 kg

Gross weight:

1,97 kg

Outer dimension, length:

615 mm

Installation depth:

80 - 140 mm

Width:

136 mm

Height:

77 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension: height

Coverage features

Type of cover: Stainless steel cover
Cover material: Stainless steel 14301
Colour of cover: silver
Frame material: Stainless steel 14301
Load class: K 3 (EN 1253-1)
Grating design: optionally tileable
Rim width: 66 mm
Rim length: 550 mm
Upper section material: ABS