

Drain body for light liq trap, w. backwater valve

Article information

Item no.: 52102
GTIN: 4026092085165
Price group: 10

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure as well as an integrated odour trap and sludge bucket. Heating oil density:

0.865 g/cm³

Variant

| | |
|--|-------|
| Emergency closure: | yes |
| Sealing water height: | 60 mm |
| Discharge rate (l/s) with 20 mm threshold: | 1 |

General characteristics

| | |
|-----------------------|----------|
| Standard: | EN 13564 |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 mm |
| Backwater protection: | Type 5 |
| Odour trap: | included |

Dimensions

| | |
|-------------------------------|-------------------------------------|
| Vertical adjustment: | 30 - 90 mm |
| Net weight: | 2,2 kg |
| Gross weight: | 2,2 kg |
| Installation depth: | 216 - 276 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Length: | 320 mm |
| Width: | 243 mm |
| Height: | 190 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-------------------------|---------|
| Material of drain body: | Polymer |
|-------------------------|---------|

Coverage features

| | |
|-------------------------|---------|
| Upper section material: | Polymer |
|-------------------------|---------|