

## Floor Tray Ferrofix glued flange H: 15 mm, 800 x 800 mm

### Article information

Item no.: 6080080  
GTIN: 4026092066492  
Price group: 03

### Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

### Description

The Ferrofix floor tray made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles. The channel profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres. The glued flange is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes.

#### Variant

Waterproofing layer on the upper section:  
Water exposure class in accordance to DIN 18534-1 (up to and including):

Adhesive flange (suitable for moisture barriers)  
W3-I

#### General characteristics

Nominal size (DN): 125  
Outer diameter (OD): 125 mm  
Glued flange height: 15 mm

#### Dimensions

Net weight: 71 kg  
Gross weight: 71,5 kg  
Length: 800 mm  
Width: 800 mm  
Height: 60 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Coverage features

Type of cover: Slotted cover  
Colour of cover: silver  
Locking: placed  
Load class: L 15 (EN 1253-1)  
Slip resistance class: R12 according to DIN 51130; C according to DIN 51097  
Upper section material: Stainless steel 14301