

Yard drain System 200, vert., slot grat., B 125

Article information

Item no.: 67922B
GTIN: 4026092038833
Price group: 10

Advantages

- Recyclable
- Fulfills highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant

System:	200
Contents of sludge trap:	yes
Discharge rate (l/s) with 20 mm threshold:	4,5

General characteristics

Nominal size (DN):	100
Odour trap:	no

Dimensions

Vertical adjustment:	40 - 150 mm
Net weight:	3,78 kg
Gross weight:	4,18 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Number of outlets:	1
Material of drain body:	Polymer
Socket version:	vertical

Coverage features

Type of cover:	Round slotted cover
----------------	---------------------

Cover material:	Ecoguss
Colour of cover:	black
Width of cover:	258 mm
Length of cover:	258 mm
Surface:	EDM
Frame material:	Ecoguss
Locking:	Lock & Lift
Load class:	B 125 (EN 124)
Rim width:	258 mm
Rim length:	258 mm
Shape of upper section:	square
Upper section material:	Ecoguss
Contents of sludge trap:	yes