

Replacement pump Aquadive GTF1200 without float switch, 10 m

Article information

Item no.: 680595
GTIN: 4026092078815
Price group: 90

Description

Replacement pump, Aquadive GTF 1200 without floater for pumping station

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight: 11,19 kg
Gross weight: 11,19 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: GTF 1200
Connection type: Schuko (earthed contact) 2-pin
Operating voltage: 230 V
Mains frequency: 50 Hz
Rated current: 6,2 A
Protection class: I
Insulation class: F
Cos phi - power factor: 0,98
Protection class (pump): IP 68
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 35 °C
Max. pumping height: 9 m
Speed: 2650 U/min
Power P1: 1,4 kW
Power P2: 0,84 kW
Operating mode: S1
Type of fuse required (electrical protection): Fuse protection through control unit 230 V
Type of pump connection cable: H07RN-F 3G 1.5 mm²
Length of mains cable for pump: 5 m

Control

Connection type:

Type of fuse required (electrical protection):

Schuko (earthed contact) 2-pin

Fuse protection through control unit 230 V