

Replacement pump GTF 600 with float switch, 10 m

Article information

Item no.: 680963
GTIN: 4026092095386
Price group: 90

Description

Replacement pump with float switch for wastewater containing faecal matter.

Variant

Pump control: **Float switch**

General characteristics

Type of wastewater: **without sewage**

Dimensions

Net weight: **6,85 kg**
Gross weight: **6,85 kg**
Packaging dimension: **length**
Packaging dimension: **width**
Packaging dimension: **height**

Pumping device

Pump: **GTF 600**
Connection type: **Schuko (earthed contact) 2-pin**
Operating voltage: **230 V**
Mains frequency: **50 Hz**
Rated current: **2,9 A**
Protection class (pump): **IP 68 (3m)**
Max. temperature (permanent) of conveyed material: **40 °C**
Max. pumping height: **8 m**
Speed: **2750 U/min**
Power P1: **0,65 kW**
Power P2: **0,4 kW**
Operating mode: **S1**
Type of fuse required (electrical protection): **C 16 A**
Type of pump connection cable: **H07RN-F 3G 1.5 mm²**
Impeller type: **Multi-vane impeller**
Length of mains cable for pump: **10 m**

Control

Connection type: **Schuko (earthed contact) 2-pin**
Type of fuse required (electrical protection): **C 16 A**