

## Backwater valve Staufix DN 200, exposed, Type 1

### Article information

Item no.: 720200  
GTIN: 4026092076118  
Price group: 10

### Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

#### Variant

Emergency closure: yes  
Mechanical backwater flaps: 1

#### General characteristics

Colour: black  
Standard: EN 13564  
Nominal size (DN): 200  
Outer diameter (OD): 200 mm  
Note on nominal size: Hydraulics correspond to DN 150  
Type of wastewater: without sewage  
Installation situation: exposed drainage pipe  
Delivery state: installation-ready  
Backwater protection: Type 1

#### Dimensions

Net weight: 3,7 kg  
Gross weight: 6,3 kg  
Vertical drop between inlet and outlet: 8 mm  
Length: 586 mm  
Width: 233 mm  
Height: 306 mm  
Packaging dimension: length

Packaging dimension:  
Packaging dimension:

width  
height

Coverage features

Type of cover:

Lockable cover

Cover locking:

One-handed closure