

## Sampling chamber DN 200, Class D

### Article information

Item no.: 915883D  
GTIN: 4026092048573  
Price group: 60

### Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

#### General characteristics

Colour: black  
Material: PE

#### Dimensions

Net weight: 48 kg  
Gross weight: 54 kg  
Vertical drop between inlet and outlet: 160 mm  
Installation depth: 950 - 1300 mm  
Type of height adjustability: vertically adjustable upper section  
Length: 730 mm  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Tank/drain body

Distance pipe bottom inlet to tank bottom: 205 mm  
Outlet nominal size (OD): 200 mm  
Outlet nominal size (DN): 200 mm  
Inlet nominal size (OD): 200 mm  
Inlet nominal size (DN): 200 mm  
Clear width of tank (LW): 450 mm

#### Coverage features

Type of cover: Cover plate  
Cover material: Grey iron  
Colour of cover: black  
Load class: D 400 (EN 124)  
Tightness: odour-tight and surface water resistant