

# Lifting stati. Aqualift F XL 300l Duo, SPF 1500-S3, Backflow preventer

## Article information

Item no.: 11032  
GTIN: 4026092056998  
Price group: 50

## Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

## Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

### Variant

Type of system: duo pump  
Shut-off valve: without shut-off valve  
Backflow preventer: integrated  
Pressure pipe connection: vertical

### General characteristics

Colour: black  
Standard: EN 12050-1  
Type of wastewater: with sewage  
Installation situation: free-standing installation  
System type: Duo

### Dimensions

Net weight: 182,57 kg  
Gross weight: 202,57 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

### Tank/drain body

Distance from centre of outlet pipe to tank bottom: 609 mm

Tank volume: 300 l

Pumping device

Pump: SPF 1500

Number of pumps: 2

Length of mains cable for pump: 5 m

Operating mode: S3 - 50 %

Impeller type: Multi-vane impeller

Free passage: 40 mm

Control

Control unit: Comfort

Level measurement instrument: Immersion pipe

Type of level measurement: pneumatic

Mains frequency: 50 Hz

Operating voltage: 400 V