

# Lifting stati. Aqualift F XL 300l Mono, SPF 1500-S3, Cast-iron shut-off val.

## Article information

Item no.: 11033  
GTIN: 4026092057001  
Price group: 50

## Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

## Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

### Variant

Type of system: Single unit  
Shut-off valve: Shut-off valve made of cast iron  
Pressure pipe connection: vertical

### General characteristics

Colour: black  
Standard: EN 12050-1  
Type of wastewater: with sewage  
Installation situation: free-standing installation  
System type: Mono

### Dimensions

Net weight: 129,86 kg  
Gross weight: 149,86 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

### Tank/drain body

Distance from centre of outlet pipe to tank bottom: 609 mm  
Tank volume: 300 l

Pumping device	
Pump:	SPF 1500
Number of pumps:	1
Length of mains cable for pump:	5 m
Operating mode:	S3 - 50 %
Impeller type:	Multi-vane impeller
Free passage:	40 mm
Control	
Control unit:	Comfort
Level measurement instrument:	Immersion pipe
Type of level measurement:	pneumatic
Mains frequency:	50 Hz
Operating voltage:	400 V