

Aqualift F XL, 200 L lift. stat. Mono, SPF 4500-S3

Article information

Item no.: 11059
GTIN: 4026092057261
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

Type of system: Single unit
Shut-off valve: without shut-off valve
Backflow preventer: integrated
Pressure pipe connection: vertical

General characteristics

Colour: black
Standard: EN 12050-1
Type of wastewater: with sewage
Installation situation: free-standing installation
System type: Mono
ATEX: no

Dimensions

Net weight: 106,39 kg
Gross weight: 126,39 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Tank volume: 200 l

Pumping device
Pump:
Number of pumps:
Operating mode:
Impeller type:
Free passage:
Length of mains cable for pump:

SPF 4500
1
S3 - 50 %
Multi-vane impeller
40 mm
5 m

Control
Control unit:
Level measurement instrument:
Type of level measurement:
Mains frequency:
Operating voltage:

Comfort
Immersion pipe
pneumatic
50 Hz
400 V