

## Lifting stati. Aqualift F XL 300l Mono, SPF 5500-S3

### Article information

Item no.: 11077  
GTIN: 4026092057445  
Price group: 50

### Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

### Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

#### Variant

Type of system: Single unit  
Shut-off valve: without shut-off valve  
Pressure pipe connection: vertical

#### General characteristics

Colour: black  
Standard: EN 12050-1  
Type of wastewater: with sewage  
Installation situation: free-standing installation  
System type: Mono

#### Dimensions

Net weight: 128,95 kg  
Gross weight: 148,95 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Tank/drain body

Tank volume: 300 l

#### Pumping device

Pump: SPF 5500

Number of pumps: 1  
Length of mains cable for pump: 5 m  
Operating mode: S3 - 30 %  
Impeller type: Multi-vane impeller  
Free passage: 40 mm

Control  
Control unit: Comfort  
Level measurement instrument: Immersion pipe  
Type of level measurement: pneumatic  
Mains frequency: 50 Hz  
Operating voltage: 400 V