

## Comfort control unit 400V, Aqualift Mono, 2.5-4.0 A

### Article information

Item no.: 28755  
GTIN: 4026092055007  
Price group: 20

### Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

### Description

Komfort control unit for lifting stations or pumping stations. Suitable for 400 V single stations. Optional connection option for float switches, conductivity probes and level probe on the terminal strip. User-friendly menu navigation in multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of the current measured values. Simple adjustment of the function-related parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signals via optional potential-free contact or integrated serial interface for GSM modem.

#### Variant

Series: ab 03/2010  
Type of system: Single unit

#### General characteristics

Colour: grey  
System type: Mono  
ATEX: no

#### Dimensions

Net weight: 2,47 kg  
Gross weight: 3,19 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Rated current: 2,5 - 4 A

| Control                        | Comfort |
|--------------------------------|---------|
| Control unit:                  | yes     |
| Motor protection switch:       | yes     |
| Protection class control unit: | IP 54   |
| Potential-free contact:        | yes     |
| GSM interface:                 | yes     |
| USB interface:                 | no      |
| Log book function:             | yes     |
| Multi-line display:            | yes     |
| Battery buffering:             | yes     |
| Self-diagnosis system (SDS):   | yes     |