

Practicus basement drain DN 100, Black grating, Horizontal outlet

Article information

Item no.: 34101
GTIN: 4026092007884
Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

| | |
|--------------------------------------------|-----|
| Contents of sludge trap: | yes |
| Discharge rate (l/s) with 10 mm threshold: | 1,1 |
| Discharge rate (l/s) with 20 mm threshold: | 1,8 |

General characteristics

| | |
|----------------------|-----------|
| Standard: | EN 1253-2 |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 mm |
| Odour trap: | no |

Dimensions

| | |
|-------------------------------|-------------------------------------|
| Net weight: | 1,39 kg |
| Gross weight: | 1,61 kg |
| Cutout dimension, width: | 180 mm |
| Cutout dimension, length: | 220 mm |
| Installation depth: | 152 - 208 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Length: | 188 mm |
| Width: | 150 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-------------------------|---------|
| Number of outlets: | 1 |
| Material of drain body: | Polymer |
| Socket version: | lateral |

Coverage features

| | |
|--------------------------|-----------------|
| Type of cover: | Slotted cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Width of cover: | 138 mm |
| Length of cover: | 138 mm |
| Surface: | Polished SST |
| Frame material: | Polymer |
| Locking: | placed |
| Load class: | K 3 (EN 1253-1) |
| Shape of upper section: | square |
| Upper section material: | Polymer |
| Contents of sludge trap: | yes |