

## Roof drain Press. fl., DN 100, with leaf trap

### Article information

Item no.: 45950  
 GTIN: 4026092001318  
 Price group: 10

### Description

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

#### Variant

System:	100
Heating:	without
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)

#### General characteristics

Nominal size (DN):	100
Outer diameter (OD):	110 mm

#### Dimensions

Net weight:	0,92 kg
Gross weight:	1,11 kg
Diameter:	246 mm
Cutout dimension, width:	180 mm
Cutout dimension, length:	180 mm
Length:	246 mm
Width:	246 mm
Height:	182 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Tank/drain body

Material of drain body:	PP
-------------------------	----

#### Coverage features

Type of cover:	Leaf trap
Cover material:	Polymer

Colour of cover:	black
Width of cover:	120 mm
Height of cover:	80 mm
Length of cover:	120 mm
Shape of upper section:	round
Upper section material:	PP